

Description

elin HHV oils are high viscosity index mineral oils based hydraulic fluids.

elin HHV oils are recommended for hydraulic or circulating oil systems, including marine on-deck machinery, hydraulic actuated loading bins, or equipment that requires a wider operating temperature as compared to a single viscosity grade oil.

Main Performance Features

1. High oxidation stability
2. Protection against rust and corrosion
3. High viscosity index (this allows a single grade of oil to be used in marine hydraulic system which operates in different climate zones).
4. Foam inhibition
5. Excellent antiwear properties
6. Good stability
7. Fast water separation
8. Good filterability
9. Low pour point properties

Typical uses

elin HHV oils are suitable for use in marine hydraulic power systems such as winches, deck cranes, steering gears, hatch cover and hydraulic valve systems etc. They may also be used in certain marine gearboxes and for turbocharger lubrication.

Requirements - Specifications

elin HHV oils meet the below requirements – specifications:

- **DIN 51524 PART III HVLP**
- **DENISON HF-O & HF-2**
- **ISO 6743-4 HV**

(*) Typical Characteristics

ISO GRADES	15	22	32	46	68	100	150
Density at 15°C, Kg/l	0,864	0,865	0,872	0,878	0,882	0,888	0,890
Kin. Viscosity at 40°C, cSt	15,8	22,5	32	46	68	100	150
Kin. Viscosity at 100°C, cSt	4,2	5,1	6,4	8,2	11	14,2	18
Viscosity Index	170	165	157	154	153	145	133
Flash point (C.O.C.), °C	175	180	190	200	205	220	250
Pour Point, °C	<-40	-36	-36	-33	-30	-30	-21

(*) (The above figures are typical of those obtained within normal production tolerances, and do not constitute a specification)

